

SOLVENT BLOCK OUT BANNER MATTE 250 (SO420)

Details

- Double layer coating on a PET & PP base, providing anti-curl properties.
- Matte finish with no glare, and excellent color density.
- Non-transmissive backside coating and Perfect background for brilliant full color prints.
- White back, Printable with Latex and UV inks
- HP Latex Certified and Roland Profiled

**Certified for
HP Latex Inks**

Specifications

Length (ft)	100	Width (inch)	36"/54"/60"
Weight (gsm)	220	Coating	Resin
Caliper (mil)	9.6	Base Material	PET & PP
Inner Core (inch)	3	Inks	
Surface	Semi-matte		

KEY FEATURES

- High Quality Image Reproduction
- Anti-Curl Properties
- Superb Blockout
- Durable for Long Term Outdoor Use
- White back, Printable with Latex and UV

Application

- Retractable Banner, Rollup Stands, Point of Purchase, Trade Show Panels, Indoor/Outdoor POP and Retail Aisle Banners

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.